
Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes single sided disk and 200,0 Gbytes double sided disk) and Quadruple Layer (128,0 Gbytes single sided disk) BD Recordable disk

Technologies de l'information — Supports enregistrés numériquement pour échange et stockage d'information — 120 mm de couche triple (100,0 Go disque unique face et 200,0 Go disque double face) et quadruple couche (128,0 Go disque unique face) sur disque enregistrable BD





COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier; Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

| | Page |
|---|-----------|
| Foreword | xi |
| Introduction | xii |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 Symbol and abbreviated terms | 2 |
| 5 Conformance | 3 |
| 5.1 Optical disk | 3 |
| 5.2 Generating system | 4 |
| 5.3 Receiving system | 4 |
| 5.4 Compatibility statement | 4 |
| 6 Convention and notations | 4 |
| 6.1 Levels of grouping | 4 |
| 6.2 Representation of numbers | 4 |
| 6.3 Integer calculus | 6 |
| 7 General description of disk | 6 |
| 8 General requirements | 8 |
| 8.1 Environments | 8 |
| 8.1.1 Test environment | 8 |
| 8.1.2 Operating environment | 8 |
| 8.1.3 Storage environment | 9 |
| 8.1.4 Transportation | 10 |
| 8.2 Safety requirements | 10 |
| 8.3 Flammability | 11 |
| 9 Reference drive | 11 |
| 9.1 General | 11 |
| 9.2 Measurement conditions | 11 |
| 9.3 Optical system | 11 |
| 9.4 Optical beam | 12 |
| 9.5 HF read channel | 13 |
| 9.6 Radial PP read channel | 14 |
| 9.7 Disk clamping | 14 |
| 9.8 Rotation of disk and measurement velocity | 14 |
| 9.9 Normalized servo transfer function | 15 |
| 9.10 Measurement velocities and reference servos for axial tracking | 15 |
| 9.10.1 General | 15 |
| 9.10.2 Reference servo for axial tracking at 1x measurement velocity | 16 |
| 9.10.3 Reference servo for axial tracking at 2x measurement velocity | 17 |
| 9.11 Measurement velocities and reference servos for radial tracking | 18 |
| 9.11.1 General | 18 |
| 9.11.2 Reference servo for radial tracking at 1x measurement velocity | 18 |
| 9.11.3 Reference servo for radial tracking at 2x measurement velocity | 20 |
| 10 Dimensional characteristics | 21 |
| 10.1 General | 21 |
| 10.2 Disk reference planes and reference axis | 22 |
| 10.3 Overall dimensions | 23 |
| 10.4 First transition area | 23 |
| 10.5 Protection ring | 24 |
| 10.6 Clamping zone | 24 |
| 10.7 Second transition area | 24 |

| | | |
|-----------|--|-----------|
| 10.8 | Information area..... | 24 |
| 10.8.1 | General..... | 24 |
| 10.8.2 | Subdivision of information zone on TL disk..... | 25 |
| 10.8.3 | Subdivision of information zone on QL disk..... | 26 |
| 10.9 | Rim area..... | 28 |
| 11 | Mechanical characteristics..... | 28 |
| 11.1 | Mass..... | 28 |
| 11.2 | Moment of inertia..... | 28 |
| 11.3 | Dynamic imbalance..... | 28 |
| 11.4 | Axial runout..... | 29 |
| 11.4.1 | General..... | 29 |
| 11.4.2 | Residual axial tracking error for 1x measurement velocity..... | 29 |
| 11.4.3 | Residual axial tracking error for 2x measurement velocity..... | 29 |
| 11.5 | Radial runout..... | 30 |
| 11.5.1 | General..... | 30 |
| 11.5.2 | Residual radial tracking error on 1x measurement velocity..... | 30 |
| 11.5.3 | Residual radial tracking error on 2x measurement velocity..... | 30 |
| 11.6 | Durability of cover layer..... | 31 |
| 11.6.1 | Impact resistance of cover layer..... | 31 |
| 11.6.2 | Scratch resistance of cover layer..... | 31 |
| 11.6.3 | Repulsion of fingerprints by cover layer..... | 31 |
| 12 | Optical characteristics in information area..... | 31 |
| 12.1 | General..... | 31 |
| 12.2 | Refractive index of the transmission stacks (TS)..... | 31 |
| 12.3 | Thickness of transmission stacks (TS)..... | 31 |
| 12.3.1 | Thickness of transmission stack of TL disks..... | 31 |
| 12.3.2 | Example of target thickness of spacer layers for TL disks..... | 32 |
| 12.3.3 | Thickness of transmission stacks of QL disks..... | 33 |
| 12.3.4 | Example of target thickness of spacer layers for QL disks..... | 34 |
| 12.4 | Reflectivity of recording layers..... | 36 |
| 12.5 | Birefringence..... | 37 |
| 12.6 | Angular deviations..... | 37 |
| 13 | Data format..... | 38 |
| 13.1 | General..... | 38 |
| 13.2 | Data frame..... | 40 |
| 13.3 | Error detection code (EDC)..... | 40 |
| 13.4 | Scrambled data frame..... | 41 |
| 13.5 | Data block..... | 41 |
| 13.6 | LDC block..... | 42 |
| 13.7 | LDC code words..... | 43 |
| 13.8 | LDC cluster..... | 44 |
| 13.8.1 | General..... | 44 |
| 13.8.2 | First interleaving step..... | 44 |
| 13.8.3 | Second interleaving step..... | 44 |
| 13.9 | Addressing and control data..... | 46 |
| 13.9.1 | General..... | 46 |
| 13.9.2 | Address units..... | 46 |
| 13.9.3 | User control data..... | 51 |
| 13.9.4 | Byte/bit assignments for user control data..... | 51 |
| 13.10 | Access block..... | 53 |
| 13.11 | BIS block..... | 53 |
| 13.12 | BIS code words..... | 54 |
| 13.13 | BIS cluster..... | 55 |
| 13.14 | ECC cluster..... | 58 |
| 13.15 | Recording frames..... | 59 |
| 13.16 | Physical cluster..... | 60 |
| 13.17 | 17PP modulation for recordable data..... | 60 |

| | | |
|-----------|---|------------|
| 13.17.1 | General | 60 |
| 13.17.2 | Bit conversion rules | 60 |
| 13.17.3 | dc-control procedure | 61 |
| 13.17.4 | Frame sync | 61 |
| 13.18 | Modulation and NRZI conversion | 63 |
| 14 | Physical data allocation and linking | 63 |
| 14.1 | General | 63 |
| 14.2 | Recording unit block (RUB) | 64 |
| 14.2.1 | General | 64 |
| 14.2.2 | Data run-in | 64 |
| 14.2.3 | Data run-out | 65 |
| 14.2.4 | Guard_3 field | 66 |
| 14.3 | Locating data relative to wobble addresses | 67 |
| 15 | Track format | 67 |
| 15.1 | General | 67 |
| 15.2 | Track shape | 67 |
| 15.3 | Track path | 69 |
| 15.4 | Track pitch | 69 |
| 15.4.1 | Track pitch in zone reserved for BCA | 69 |
| 15.4.2 | Track pitch in embossed HFM area | 69 |
| 15.4.3 | Track pitch in recordable areas | 70 |
| 15.4.4 | Track pitch between embossed HFM area and recordable area | 70 |
| 15.5 | Track layout of HFM groove | 70 |
| 15.5.1 | General | 70 |
| 15.5.2 | Data format | 71 |
| 15.5.3 | Addressing and control data | 72 |
| 15.5.4 | Recording frames | 75 |
| 15.6 | Track layout of wobbled grooves | 77 |
| 15.6.1 | General | 77 |
| 15.6.2 | Modulation of wobbles | 78 |
| 15.6.3 | Wobble polarity | 79 |
| 15.7 | ADIP information | 79 |
| 15.7.1 | General | 79 |
| 15.7.2 | ADIP unit types | 80 |
| 15.7.3 | ADIP word structure | 81 |
| 15.7.4 | ADIP data structure | 82 |
| 15.7.5 | ADIP error correction | 86 |
| 15.8 | Disk information in ADIP aux frame | 88 |
| 15.8.1 | General | 88 |
| 15.8.2 | Error protection for disk information aux frames | 89 |
| 15.8.3 | Disk information data structure | 90 |
| 16 | General description of information zone | 137 |
| 16.1 | General | 137 |
| 16.2 | Format of information zone on triple-layer disk | 137 |
| 16.3 | Format of information zone on quadruple-layer disk | 137 |
| 17 | Layout of recordable area of information zone | 137 |
| 18 | Inner zone(s) | 146 |
| 18.1 | General | 146 |
| 18.2 | Permanent information and control data (PIC) zone | 153 |
| 18.2.1 | General | 153 |
| 18.2.2 | Content of PIC zone | 153 |
| 18.2.3 | Emergency brake | 155 |
| 18.3 | Recordable area of lead-in zone of TL disk | 157 |
| 18.3.1 | Protection zone 2 | 157 |
| 18.3.2 | Buffer | 157 |
| 18.3.3 | INFO 2/Reserved 8 | 157 |

| | | |
|---------|--|-----|
| 18.3.4 | INFO 2/Reserved 7 | 157 |
| 18.3.5 | INFO 2/Reserved 6 | 157 |
| 18.3.6 | INFO 2/Reserved 5 | 158 |
| 18.3.7 | INFO 2/PAC 2 | 158 |
| 18.3.8 | INFO 2/DMA 2 | 158 |
| 18.3.9 | INFO 2/Control data 2 | 158 |
| 18.3.10 | INFO 2/Buffer 2 | 158 |
| 18.3.11 | OPC 0/Test zone | 158 |
| 18.3.12 | Usage of OPC areas | 158 |
| 18.3.13 | OPC 0/OPC 0 buffer | 160 |
| 18.3.14 | TDMA 0 | 160 |
| 18.3.15 | INFO 1/Pre-write area | 160 |
| 18.3.16 | INFO 1/Drive area | 160 |
| 18.3.17 | INFO 1/DMA 1 | 161 |
| 18.3.18 | INFO 1/Control data 1 | 161 |
| 18.3.19 | INFO 1/PAC 1 | 161 |
| 18.4 | Recordable area of inner zone 1 of TL disk | 161 |
| 18.4.1 | Buffer | 161 |
| 18.4.2 | OPC 1/Test zone | 161 |
| 18.4.3 | Reserved | 162 |
| 18.4.4 | INFO 2/Reserved 8 | 162 |
| 18.4.5 | INFO 2/Reserved 7 | 162 |
| 18.4.6 | INFO 2/Reserved 6 | 162 |
| 18.4.7 | INFO 2/Reserved 5 | 162 |
| 18.4.8 | INFO 2/PAC 2 | 162 |
| 18.4.9 | INFO 2/DMA 2 | 162 |
| 18.4.10 | INFO 2/Control data 2 | 162 |
| 18.4.11 | INFO 2/Buffer 2 | 162 |
| 18.4.12 | TDMA 1 | 162 |
| 18.4.13 | Reserved | 163 |
| 18.4.14 | INFO 1/Pre-write area | 163 |
| 18.4.15 | INFO 1/Drive area | 163 |
| 18.4.16 | INFO 1/DMA 1 | 163 |
| 18.4.17 | INFO 1/Control data 1 | 163 |
| 18.4.18 | INFO 1/PAC 1 | 163 |
| 18.5 | Recordable area of inner zone 2 of TL disk | 163 |
| 18.5.1 | Buffer | 163 |
| 18.5.2 | OPC 2/Test zone | 163 |
| 18.5.3 | OPC 2/OPC 2 buffer | 163 |
| 18.5.4 | Reserved | 163 |
| 18.5.5 | INFO 2/Reserved 8 | 163 |
| 18.5.6 | INFO 2/Reserved 7 | 164 |
| 18.5.7 | INFO 2/Reserved 6 | 164 |
| 18.5.8 | INFO 2/Reserved 5 | 164 |
| 18.5.9 | INFO 2/Reserved | 164 |
| 18.5.10 | INFO 2/DMA 2 | 164 |
| 18.5.11 | INFO 2/Control data 2 | 164 |
| 18.5.12 | INFO 2/Buffer 2 | 164 |
| 18.5.13 | TDMA 2 | 164 |
| 18.5.14 | Buffer | 164 |
| 18.5.15 | INFO 1/Pre-write area | 164 |
| 18.5.16 | INFO 1/Drive area | 165 |
| 18.5.17 | INFO 1/DMA 1 | 165 |
| 18.5.18 | INFO 1/Control data 1 | 165 |
| 18.5.19 | INFO 1/Reserved | 165 |
| 18.6 | Recordable area of lead-in zone of QL disk | 165 |
| 18.6.1 | Protection zone 2 | 165 |
| 18.6.2 | Buffer | 165 |

| | | |
|---------|---|-----|
| 18.6.3 | INFO 2/Reserved 8 | 165 |
| 18.6.4 | INFO 2/Reserved 7 | 165 |
| 18.6.5 | INFO 2/Reserved 6 | 165 |
| 18.6.6 | INFO 2/Reserved 5 | 165 |
| 18.6.7 | INFO 2/PAC 2 | 166 |
| 18.6.8 | INFO 2/DMA 2 | 166 |
| 18.6.9 | INFO 2/Control data 2 | 166 |
| 18.6.10 | INFO 2/Buffer 2 | 166 |
| 18.6.11 | OPC 0/Test zone | 166 |
| 18.6.12 | Buffer | 166 |
| 18.6.13 | INFO 1/Pre-write area | 166 |
| 18.6.14 | INFO 1/Drive area | 166 |
| 18.6.15 | INFO 1/DMA 1 | 166 |
| 18.6.16 | INFO 1/Control data 1 | 166 |
| 18.6.17 | INFO 1/PAC 1 | 167 |
| 18.7 | Recordable area of inner zone 1 of QL disk | 167 |
| 18.7.1 | Buffer | 167 |
| 18.7.2 | OPC 1/Test zone | 167 |
| 18.7.3 | INFO 2/Reserved 8 | 167 |
| 18.7.4 | INFO 2/Reserved 7 | 167 |
| 18.7.5 | INFO 2/Reserved 6 | 167 |
| 18.7.6 | INFO 2/Reserved 5 | 167 |
| 18.7.7 | INFO 2/PAC 2 | 167 |
| 18.7.8 | INFO 2/DMA 2 | 167 |
| 18.7.9 | INFO 2/Control data 2 | 168 |
| 18.7.10 | INFO 2/Buffer 2 | 168 |
| 18.7.11 | TDMA 0 | 168 |
| 18.7.12 | Buffer | 168 |
| 18.7.13 | INFO 1/Pre-write area | 168 |
| 18.7.14 | INFO 1/Drive area | 168 |
| 18.7.15 | INFO 1/DMA 1 | 168 |
| 18.7.16 | INFO 1/Control data 1 | 168 |
| 18.7.17 | INFO 1/PAC 1 | 168 |
| 18.8 | Recordable area of inner zone 2 of QL disk | 168 |
| 18.8.1 | Buffer | 168 |
| 18.8.2 | INFO 2/Reserved 8 | 168 |
| 18.8.3 | INFO 2/Reserved 7 | 169 |
| 18.8.4 | INFO 2/Reserved 6 | 169 |
| 18.8.5 | INFO 2/Reserved 5 | 169 |
| 18.8.6 | INFO 2/Reserved | 169 |
| 18.8.7 | INFO 2/DMA 2 | 169 |
| 18.8.8 | INFO 2/Control data 2 | 169 |
| 18.8.9 | INFO 2/Buffer 2 | 169 |
| 18.8.10 | TDMA 1 | 169 |
| 18.8.11 | Buffer | 169 |
| 18.8.12 | OPC 2/Test zone | 169 |
| 18.8.13 | OPC 2/OPC 2 buffer | 170 |
| 18.8.14 | TDMA 2 | 170 |
| 18.8.15 | INFO 1/Pre-write area | 170 |
| 18.8.16 | INFO 1/Drive area | 170 |
| 18.8.17 | INFO 1/DMA 1 | 170 |
| 18.8.18 | INFO 1/Control data 1 | 170 |
| 18.8.19 | INFO 1/Reserved | 170 |
| 18.9 | Recordable area of lead-out zone of QL disk | 170 |
| 18.9.1 | OPC 3/Test zone | 170 |
| 18.9.2 | Buffer | 170 |
| 18.9.3 | INFO 2/Reserved 8 | 170 |
| 18.9.4 | INFO 2/Reserved 7 | 171 |

| | | |
|-----------|---|------------|
| 18.9.5 | INFO 2/Reserved 6 | 171 |
| 18.9.6 | INFO 2/Reserved 5 | 171 |
| 18.9.7 | INFO 2/Reserved | 171 |
| 18.9.8 | INFO 2/DMA 2 | 171 |
| 18.9.9 | INFO 2/Control data 2 | 171 |
| 18.9.10 | INFO 2/Buffer 2 | 171 |
| 18.9.11 | TDMA 3 | 171 |
| 18.9.12 | INFO 1/Pre-write area | 171 |
| 18.9.13 | INFO 1/Drive area | 171 |
| 18.9.14 | INFO 1/DMA 1 | 172 |
| 18.9.15 | INFO 1/Control data 1 | 172 |
| 18.9.16 | INFO 1/Reserved | 172 |
| 19 | Data zone | 172 |
| 20 | Outer zones | 172 |
| 20.1 | General | 172 |
| 20.2 | Recordable area of outer zones | 174 |
| 20.2.1 | INFO 3/Buffer 4 | 174 |
| 20.2.2 | INFO 3/DMA 3 | 174 |
| 20.2.3 | INFO 3/Control data 3 | 174 |
| 20.2.4 | Angular buffer | 174 |
| 20.2.5 | INFO 4/DMA 4 | 174 |
| 20.2.6 | INFO 4/Control data 4 | 174 |
| 20.2.7 | INFO 4/Buffer 6 | 174 |
| 20.2.8 | DCZ 0/Test zone, DCZ 1/Test zone, DCZ 2/Test zone and DCZ 3/Test zone | 174 |
| 20.2.9 | Usage of DCZ area | 174 |
| 20.2.10 | Protection zone 3 | 176 |
| 21 | Physical access control clusters | 176 |
| 21.1 | General | 176 |
| 21.2 | Layout of PAC zones | 177 |
| 21.3 | General structure of PAC clusters | 177 |
| 21.4 | IS1 and IS2 PAC clusters | 181 |
| 22 | Disk management | 181 |
| 22.1 | General | 181 |
| 22.2 | Recording management | 182 |
| 22.2.1 | General | 182 |
| 22.2.2 | Sequential recording mode (SRM) | 182 |
| 22.2.3 | Recording user data in SRR | 182 |
| 22.2.4 | SRR status | 182 |
| 22.2.5 | Closing SRR | 183 |
| 22.3 | Temporary disk management areas (TDMA) | 183 |
| 22.3.1 | General | 183 |
| 22.3.2 | TDMA access indicators | 183 |
| 22.4 | Disk management structure (DMS) | 184 |
| 22.4.1 | General | 184 |
| 22.4.2 | Temporary disk management structure (TDMS) | 184 |
| 22.4.3 | TDMS in sequential recording mode | 185 |
| 22.4.4 | Temporary disk definition structure (TDDS) | 186 |
| 22.4.5 | Temporary defect list (TDFL) | 191 |
| 22.4.6 | Sequential recording range information (SRR I) | 193 |
| 22.5 | Unrecorded (blank) disk structure | 195 |
| 22.5.1 | General | 195 |
| 22.5.2 | Pre-recorded areas on unrecorded disk | 195 |
| 22.5.3 | Pre-recorded BCA | 202 |
| 22.5.4 | Pre-recorded INFO 2/Reserved 5, Reserved 8 and Pre-recorded INFO 1/ Pre-write area | 202 |
| 22.5.5 | Pre-recorded INFO 1/PAC 1 and Pre-recorded INFO 2/PAC 2 | 202 |

| | | |
|-----------|---|------------|
| 22.5.6 | OPC 0/Test zone, OPC 1/Test zone, OPC 2/Test zone and OPC 3/Test zone | 202 |
| 22.5.7 | TDMA 0 | 203 |
| 22.5.8 | Initialization of disk | 203 |
| 22.6 | Recorded (closed) disk structure | 203 |
| 22.6.1 | General | 203 |
| 22.6.2 | DMA zones | 203 |
| 22.6.3 | Disk management structure (DMS) | 204 |
| 23 | Assignment of logical sector numbers (LSNs) | 206 |
| 24 | Characteristics of grooved areas | 207 |
| 25 | Method of testing for grooved area | 208 |
| 25.1 | General | 208 |
| 25.2 | Environment | 208 |
| 25.3 | Reference drive | 208 |
| 25.3.1 | General | 208 |
| 25.3.2 | Read power | 208 |
| 25.3.3 | Read channels | 208 |
| 25.3.4 | Tracking requirements | 208 |
| 25.3.5 | Scanning velocities | 208 |
| 25.4 | Definition of signals | 209 |
| 26 | Signals from HFM grooves | 210 |
| 26.1 | Push-pull polarity | 210 |
| 26.2 | Push-pull signal | 210 |
| 26.3 | Wobble signal | 210 |
| 26.4 | Jitter of HFM signal | 210 |
| 27 | Signals from wobbled grooves | 211 |
| 27.1 | Phase depth | 211 |
| 27.2 | Push-pull signal | 211 |
| 27.3 | Wobble signal | 211 |
| 27.3.1 | General | 211 |
| 27.3.2 | Measurement of I_{NWS} | 212 |
| 27.3.3 | Measurement of wobble CNR | 212 |
| 27.3.4 | Measurement of harmonic distortion of wobble | 212 |
| 28 | Characteristics of recording layer | 212 |
| 29 | Method of testing for recording layer | 213 |
| 29.1 | General | 213 |
| 29.2 | Environment | 213 |
| 29.3 | Reference drive | 213 |
| 29.3.1 | General | 213 |
| 29.3.2 | Read power | 213 |
| 29.3.3 | Read channels | 213 |
| 29.3.4 | Tracking requirements | 213 |
| 29.3.5 | Scanning velocities | 213 |
| 29.4 | Write conditions | 214 |
| 29.4.1 | Write pulse waveform | 214 |
| 29.4.2 | Write powers | 214 |
| 29.4.3 | Average power | 215 |
| 29.4.4 | Write conditions for i-MLSE measurement | 215 |
| 29.5 | Definition of signals | 215 |
| 30 | Signals from recorded areas | 215 |
| 30.1 | HF signals | 215 |
| 30.2 | Modulated amplitude | 215 |
| 30.3 | Reflectivity-modulation product | 217 |
| 30.4 | Asymmetry | 217 |
| 30.5 | i-MLSE | 217 |

| | | |
|---|---|------------|
| 30.6 | Read stability..... | 218 |
| 31 | Local defects..... | 219 |
| 32 | Characteristics of user data..... | 219 |
| 33 | Method of testing for user data..... | 219 |
| 33.1 | General..... | 219 |
| 33.2 | Environment..... | 220 |
| 33.3 | Reference drive..... | 220 |
| 33.3.1 | General..... | 220 |
| 33.3.2 | Read power..... | 220 |
| 33.3.3 | Read channels..... | 220 |
| 33.3.4 | Error correction..... | 220 |
| 33.3.5 | Tracking requirements..... | 220 |
| 33.3.6 | Scanning velocities..... | 220 |
| 33.4 | Error signals..... | 220 |
| 34 | Minimum quality of recorded information..... | 222 |
| 34.1 | Symbol error rate..... | 222 |
| 34.2 | Maximum burst errors..... | 222 |
| 34.3 | User-written data..... | 222 |
| 35 | BCA..... | 222 |
| Annex A (normative) Thickness of transmission stacks in case of multiple layers..... | | 224 |
| Annex B (normative) Measurement of reflectivity..... | | 227 |
| Annex C (normative) Measurement of scratch resistance of cover layer..... | | 232 |
| Annex D (normative) Measurement of repulsion of grime by cover layer..... | | 234 |
| Annex E (normative) Measurement of wobble amplitude..... | | 237 |
| Annex F (normative) Write pulse waveform for testing..... | | 242 |
| Annex G (normative) Optimum power control (OPC) procedure for disk..... | | 250 |
| Annex H (normative) HF signal pre-processing for i-MLSE(integrated maximum likelihood sequence error estimation) measurements..... | | 254 |
| Annex I (normative) Measurement procedures..... | | 266 |
| Annex J (informative) Measurement of birefringence..... | | 278 |
| Annex K (informative) Measurement of thickness of cover layer and spacer layer..... | | 280 |
| Annex L (informative) Measurement of impact resistance of cover layer..... | | 283 |
| Annex M (informative) Groove deviation and the wobble amplitude..... | | 285 |
| Annex N (informative) Guideline for write pulse adjustment using L-SEAT edge shift..... | | 287 |
| Annex O (normative) Specific requirements for type TL/D disk..... | | 295 |
| Annex P (informative) Bonding of type TL/D disk..... | | 297 |
| Bibliography..... | | 298 |

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <http://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information Technology*, Subcommittee SC 23, *Digitally recorded media for information interchange and storage*.

This third edition cancels and replaces the second edition (ISO/IEC 30191:2015), which has been technically revised. It also incorporates the Amendment ISO/IEC 30191:2015/Amd.1 :2019.

The main change compared to the previous edition is the addition of requirements for physical access control and reserved area of BD application.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In March 2002, the Blu-ray Disc Founders, or BDF, came together to create optical disk formats with the large capacity and high-speed transfer rates that would be needed for recording and reproducing high-definition video content.

The Blu-ray Disc Association (BDA) issued the first version of the Blu-ray Disc™ Recordable Format Part 1 in October 2005, and Version 1.3 of the Blu-ray Disc™ Recordable Format Part 1 in April 2008, which enabled the recording velocity up to 6x. In June 2010, the BDA issued Blu-ray Disc™ Recordable Format Part 1 Version 2.0, which specifies the TL and QL of BD recordable disk.

To keep the compatibility of the removable medium in the market, just to make a standard is not enough, and it is necessary to check that the disks and devices can satisfy the specifications. The BDA also conducts verification activities for the disks and devices and has established more than 10 testing centers in Asia, Europe and the USA.

Blu-ray™ disks, players, recorders and PC drives/software based on BDA standards became popular all over the world. The BDA gave consumer applications the highest priority in the first few years. But it was known, of course, that international standardization would be required before many government entities and their contractors would be allowed to use Blu-ray Disc™. In January and February 2011, the BDA was formally requested to consider international standardization. The reason for this was to enable the inclusion of writable BDs, along with DVDs and CDs, in an International Standard specifying test methods for the estimation of lifetime of optical storage media for long-term data storage. In October 2011, the BDA responded that it had decided to pursue international standardization of the basic physical formats for the Recordable and Rewritable Blu-ray™ Format.

In December 2011, the BDA sent project proposals for international standardization of four formats. ISO/IEC 30190, ISO/IEC 30191, ISO/IEC 30192 and ISO/IEC 30193 were published in 2013.

A few additional specifications are required in order to write and read video-recording applications, such as the BDMV and BDAV formats, which have been specified by the BDA for use on BD recordable disks. These specifications, which are related to the BD application, the file system or the content protection system, are required for the disk, the generating system and the receiving system¹⁾.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO and IEC take no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured ISO and IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO and IEC. Information may be obtained from the patent database available at www.iso.org/patents.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those in the patent database. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Blu-ray™, Blu-ray Disc™ and the logos are trademarks of the Blu-ray Disc Association.

1) For more information of the BD application, the content-protection system and the additional requirements for the Blu-ray™ Format specifications, see <http://www.blu-raydisc.info>.

Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes single sided disk and 200,0 Gbytes double sided disk) and Quadruple Layer (128,0 Gbytes single sided disk) BD Recordable disk

1 Scope

This document specifies the mechanical, physical and optical characteristics of a 120 mm recordable optical disk with a capacity of 100,0 Gbytes, 128,0 Gbytes or 200,0 Gbytes. It specifies the quality of the recorded and unrecorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. User data can be written once and read many times using a non-reversible method. This disk is identified as BD recordable disk.

This document specifies the following:

- three related but different types of this disk;
- the conditions for conformance;
- the environments in which the disk is to be operated and stored;
- the mechanical and physical characteristics of the disk, so as to provide mechanical interchange between data processing systems;
- the format of the information on the disk, including the physical disposition of the tracks and sectors;
- the error correcting codes and the coding method used;
- the characteristics of the signals recorded on the disk, enabling data processing systems to read the data from the disk.

This document provides for interchange of disks between disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 646, *Information technology — ISO 7 bit coded character set for information interchange*

ISO 9352, *Plastics — Determination of resistance to wear by abrasive wheels*

ISO/IEC 30193, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk*

IEC 60068-2-2, *Environmental testing — Part 2-2: Tests — Test B: Dry heat*

IEC 60068-2-30, *Environmental testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 h + 12 h cycle)*

IEC 60950-1, *Information technology equipment — Safety — Part 1: General requirements*