

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
8802-15-3

First edition
2017-10

**Information technology —
Telecommunications and information
exchange between systems — Local
and metropolitan area networks —
Specific requirements —**

**Part 15-3:
High data rate wireless multi-media
networks**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux locaux et métropolitains —
Exigences spécifiques —*

Partie 15-3: Réseaux multimédias sans fil à haut débit de données



Reference number
ISO/IEC/IEEE 8802-15-3:2017(E)

© IEEE 2016



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO or IEEE at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

stds.ipr@ieee.org
www.ieee.org

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and nongovernmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of ISO/IEC JTC 1 is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. ISO/IEEE is not responsible for identifying essential patents or patent claims for which a license may be required, for conducting inquiries into the legal validity or scope of patents or patent claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance or a Patent Statement and Licensing Declaration Form, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from ISO or the IEEE Standards Association.

ISO/IEC/IEEE 8802-15-3 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std. 802.15.3:2016). It was adopted by Joint Technical Committee ISO/IEC JTC 1, *Information technology, Subcommittee SC 6, Telecommunications and information exchange between systems*, in parallel with its approval by the ISO/IEC national bodies, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE. IEEE is responsible for the maintenance of this document with participation and input from ISO/IEC national bodies.

IEEE Std 802.15.3™-2016
(Revision of
IEEE Std 802.15.3-2003)

IEEE Standard for High Data Rate Wireless Multi-Media Networks

Sponsor

LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 15 May 2016
IEEE-SA Standards Board

Abstract: The protocol and compatible interconnection of data and multimedia communication equipment via 2.4 GHz and 60 GHz radio transmissions in a Wireless Personal Area Network (WPAN) using low power and multiple modulation formats to support scalable data rates is defined in this standard. The Medium Access Control (MAC) sublayer protocol supports both isochronous and asynchronous data types.

Keywords: ad hoc network, IEEE 802.15.3™, mobility, mm-wave, radio frequency, wireless

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2016 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 25 July 2016. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-2023-5 STD20940
Print: ISBN 978-1-5044-2024-2 STDPD20940

IEEE prohibits discrimination, harassment, and bullying. For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/browse/standards/collection/ieee> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this standard was completed, the IEEE 802.15 working group had the following membership:

IEEE 802.15 Working group

Robert F. Heile, *Working Group Chair*

Rick Alfvén, *Working Group Vice-Chair*

Patrick Kinney, *Working Group Vice-Chair, Working Group Secretary*

James P. K. Gilb, *Working Group Technical Editor*

Benjamin A. Rolfe, *Working Group Treasurer*

James P. K. Gilb, *802.15.3m Chair, 802.15.3RevA Technical Editor*

Mohamed Abdallah	Yeong Min Jang	John Notor
Keiji Akiyama	Seong-Soon Joo	Hiroyo Ogawa
Hideki Aoyama	Volker Jungnickel	Mitsuaki Oshima
Arthur Astrin	Jeritt Kent	Chandrashekha P. S. Bhat
Tuncer Baykas	Jaehwan Kim	Glenn Parsons
Philip Beecher	Junhyeong Kim	Charles Perkins
Monique Brown	Young-Hoon Kim	Albert Petrick
Kiran Bynam	Youngsoo Kim	Clinton Powell
Edgar Callaway	Shoichi Kitazawa	Verotiana Rabarijaona
Chris Calvert	Tero Kivinen	Demir Rakanovic
Radhakrishna Canchi	Ryuji Kohno	Ivan Reede
Jaesang Cha	Fumihide Kojima	Richard Roberts
Soo-Young Chang	Keitarou Kondou	Noriyuki Sato
Clint Chaplin	Thomas Kuerner	Norihiko Sekine
Stephen Chasko	Amarjeet Kumar	Nikola Serafimovski
Sangsung Choi	Byung-Jae Kwak	Kunal Shah
Hee-Sang Chung	Namtuan Le	Stephen Shellhammer
Hendricus De Ruijter	Hoosung Lee	Shusaku Shimada
Guido Dolmans	Jae Seung Lee	Gyung Chul Sihn
Igor Dotlic	Moon-Sik Lee	Gary Stuebing
Andrew Estrada	Myung Lee	Don Sturek
David Evans	Huan-Bang Li	Mineo Takai
Kiyoshi Fukui	Liang Li	Kou Togashi
Tim Godfrey	Michael Lynch	Kiyoshi Toshimitsu
Yoshiho Goto	Itaru Maekawa	Murat Uysal
Jussi Haapola	Hiroyuki Matsumura	Billy Verso
Shinsuke Hara	Kenichi Mori	Brian Weis
Marco Hernandez	Robert Moskowitz	Makoto Yaita
Ken Hiraga	Mohammad Nekoui	Peter Yee
Jay Holcomb	Chiu Ngo	Hidetoshi Yokota
Koji Horisaki	Trang Nguyen	Yu Zeng
Iwao Hosako	Paul Nikolich	Junwen Zhang
Bing Hui	Makoto Noda	Chunhui Zhu

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Tomoko Adachi	Noriyuki Ikeuchi	Satoshi Oyama
Thomas Alexander	Yasuhiko Inoue	Tomas Pajda
Richard Alfvén	Sergiu Iordanescu	Arumugam Paventhan
James D. Allen	Paul Isaacs	Dalibor Pokrajac
Nobumitsu Amachi	Akio Iso	Clinton Powell
Carol Ansley	Atsushi Ito	Venkatesha Prasad
Yusuke Asai	Adri Jovin	Demir Rakanovic
Alfred Asterjadhi	Shinkyō Kaku	R. K. Rannow
Gennaro Boggia	Piotr Karocki	James Reilly
Nancy Bravin	Jeritt Kent	Maximilian Riegel
William Byrd	Stuart Kerry	Robert Robinson
Radhakrishna Canchi	Yongbum Kim	Benjamin Rolfe
William Carney	Patrick Kinney	Naotaka Sato
Juan Carreon	Tero Kivinen	Frank Schewe
Yesenia Cevallos	Adrian Kliks	Reinhard Schrage
Minho Cheong	Yasushi Kudoh	Andy Scott
Peter Cibula	Thomas Kuerner	Michael Seaman
Charles Cook	Thomas Kurihara	Daniel Smolinski
Richard Doyle	Paul Lambert	Manikantan Srinivasan
Constantin Dumitrescu	Jeremy Landt	Dorothy Stanley
Sourav Dutta	Joseph Levy	Thomas Starai
Richard Edgar	Arthur H. Light	Eugene Stoudenmire
David Evans	William Lumpkins	Rene Struik
Liu Fangfang	Michael Lynch	Walter Struppler
Avraham Freedman	Elvis Maculuba	Mark Sturza
Yukihiro Fujimoto	Jeffery Maki	David Thompson
Yue Gao	Roger Marks	Pedro Tonhozi de Oliveira
Alexander Gelman	Jeffery Masters	Lorenzo Vangelista
James P. K. Gilb	Michael McInnis	Dmitri Varsanofiev
Eric W. Gray	Richard Mellitz	Prabodh Varshney
Randall Groves	Juichi Nakada	George Vlantis
Michael Gundlach	Nabil Nasser	Hung-Yu Wei
Robert F. Heile	Michael Newman	Andreas Wolf
Jerome Henry	Chiu Ngo	Chun Yu Charles Wong
Marco Hernandez	Nick S.A. Nikjoo	Oren Yuen
Werner Hoelzl	Makoto Noda	Zhen Zhou
Rita Horner	John Notor	

When the IEEE-SA Standards Board approved this standard on 15 May 2016, it had the following membership:

Jean-Philippe Faure, *Chair*
Ted Burse, *Vice-Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Chuck Adams	Ronald W. Hotchkiss	Mehmet Ulema
Masayuki Ariyoshi	Michael Janezic	Yingli Wen
Stephen Dukes	Joseph L. Koepfinger*	Howard Wolfman
Jianbin Fan	Hung Ling	Don Wright
J. Travis Griffith	Kevin Lu	Yu Yuan
Gary Hoffman	Annette D. Reilly	Daidi Zhong
	Gary Robinson	

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.15.3-2016, IEEE Standard for High Data Rate Wireless Multi-Media Networks.

IEEE Std 802.15.3-2016 was originally developed to provide superior quality of service (QoS) over relatively medium range wireless links.

The idea of a high-rate addition to the IEEE 802.15 family of standards was first proposed in November 1999 at the IEEE Plenary meeting in Kaua'i, HI. The 802.15.3 task group began its official work at the March 2000 IEEE Plenary meeting in Albuquerque, NM, creating a criteria document and evaluation method. The down-selection of MAC and PHY proposals was completed at the November 2000 IEEE 802 Plenary meeting in Tampa, FL, and the writing of the draft began in December 2000. After working on the draft for one year, the document was ready for the task group ballot process in December 2001. The draft received final working group approval at the November 2002 IEEE Plenary meeting in Kaua'i, HI, and began the sponsor ballot process following the meeting. The draft went through one sponsor ballot and two recirculations before it was submitted to the IEEE Standards Association Standards Board (IEEE-SASB) for approval. The IEEE-SASB approved 802.15.3 as an IEEE standard in June 2003.

IEEE Std 802.15.3-2003 defined an ad-hoc MAC that enabled simple and fast network formation, excellent QoS, strong security with 128-bit AES encryption in CCM mode and methods to coexist with other wireless networks in the band. The PHY operated in the license exempt 2.4 GHz band with data rates of 11 Mb/s to 55 Mb/s at distances of greater than 70 m.

Interest in working on an amendment to fix and enhance IEEE Std 802.15.3 began in the September 2003 meeting in Singapore. A study group was formed at the November 2003 meeting in Albuquerque, which completed a project authorization request that was approved in March 2004. Work progressed quickly, and the first task group letter ballot was successfully completed in March 2005. After one recirculation, the draft began sponsor ballot in August 2005. The ballot was successful, and after a recirculation ballot to validate some minor changes, IEEE Std 802.15.3b was approved by the IEEE Standards Board on 6 December 2005, just over two years after the study group started.

IEEE Std 802.15.3b-2005 fixed mistakes and added enhancements that improve the efficiency of the base standard. Some of the key changes/additions in this amendment are as follows:

- An improved definition of the medium access control (MAC) layer management entity (MLME) service access point (SAP).
- A new acknowledgment (ACK) policy, implied-ACK, which allows polling and a more efficient use of channel time.
- A method for relinquishing time in a channel time allocation (CTA) to allow another device (DEV) time to transmit data.
- The ability to assign device identifiers (DEVIDs) to group addresses to allow multicast connections.
- Faster recovery of network operations when the piconet coordinator (PNC) abruptly disconnects\ with the conditional handover and the next PNC processes.
- Multiple contention periods during a superframe.

In the July 2003 meeting in San Francisco, an interest group was formed to consider a mmWave PHY for the existing standard. A study group was formally created in the March 2004 IEEE 802 plenary meeting in Orlando and developed a project authorization request that was approved in March 2005. The first meeting as a task group was in May 2005 in Cairns, Australia and the group worked steadily developing channel models and evaluation documents. The PHY modes were selected in November 2007 at the Atlanta meeting

IEEE Std 802.15.3-2016
IEEE Standard for High Data Rate Wireless Multi-Media Networks

and draft progressed rapidly, entering working group letter ballot in June 2008. After three working group recirculation ballots, sponsor ballot started in March 2009. A total of three sponsor recirculation ballots were held, leading to approval of IEEE Std 802.15.3c-2009 by the IEEE-SA Standards Board on 11 September 2009.

Some of the key features of IEEE Std 802.15.3c-2009 and additions are as follows:

- Operation in the 60 GHz band.
- New data rates, with the highest greater than 5 Gb/s.
- Beamforming negotiation for the transmitter to increase the communication range.
- MAC packet aggregation and the acknowledgment of individual subpackets to reduce retransmission overhead.

The PHY specifies three modes and one common mode. The three PHY modes are as follows:

- Single carrier (SC) mode optimized for low power and low complexity.
- High-speed interface (HSI) mode optimized for low-latency bidirectional data transfer.
- Audio/video (AV) mode optimized for the delivery of uncompressed, high-definition video and audio.

In 2015, there were two new projects that wanted to add additional optional PHYs. To support the development of these new amendments, the base standard needed to be revised to create a single document that incorporated the prior two amendments. A PAR was generated in July 2015 at the IEEE Plenary meeting in Waikoloa Village, HI. The PAR was approved by the IEEE SASB in September 2015 and the initial draft was completed soon thereafter (by the same Technical Editor who worked on the previous three documents). After two working group ballots, the sponsor ballot began in December 2015 and completed in February 2016 after two Sponsor ballot recirculations. IEEE Std 802.15.3-2016 was approved by the IEEE-SA Standards Board in May 2016.

Contents

1.	Overview.....	26
1.1	Scope.....	26
1.2	Purpose.....	26
2.	Normative references.....	27
3.	Definitions, acronyms, and abbreviations.....	28
3.1	Definitions.....	28
3.2	Acronyms and abbreviations.....	29
4.	General description.....	33
4.1	What is a piconet?.....	33
4.2	Components of an IEEE 802.15.3 piconet.....	33
4.3	Overview of medium access control (MAC) functionality.....	33
4.3.1	Coordination.....	34
4.3.1.1	Starting a piconet.....	34
4.3.1.2	Handing over control of the piconet.....	34
4.3.1.3	Creating a child piconet.....	34
4.3.1.4	Creating a neighbor piconet.....	35
4.3.2	Ending a piconet.....	35
4.3.3	Ending a piconet with a dependent piconet involved.....	35
4.3.4	Association and disassociation.....	36
4.3.5	Security overview.....	36
4.3.6	The IEEE 802.15.3 superframe.....	36
4.3.7	Channel time management.....	37
4.3.8	Data communications between DEVs.....	38
4.3.9	Information discovery in the piconet.....	38
4.3.10	Dynamic channel selection.....	39
4.3.11	Power management.....	39
4.3.12	Controlling transmit power in the piconet.....	40
4.3.13	Superframe structure using quasi-omni mode.....	40
4.3.14	Frame aggregation.....	41
4.3.15	Beam forming.....	41
4.3.16	Channel probing.....	41
4.3.17	Unequal error protection (UEP).....	41
4.4	Characteristics of the 2.4 GHz PHY.....	41
4.4.1	General characteristics.....	41
4.4.2	Coexistence and interoperability.....	42
4.5	Characteristics of the mmWave PHY.....	42
4.5.1	mmWave PHY characteristics.....	42
4.5.2	Piconets using mmWave PHY modes.....	43
4.6	Conventions.....	44
4.7	Concept of primitives.....	44
5.	Layer management.....	46
5.1	Overview of management model.....	46
5.2	Generic management primitives.....	47
5.2.1	MLME-GET.request.....	48

5.2.2	MLME-GET.confirm	48
5.2.3	MLME-SET.request	48
5.2.4	MLME-SET.confirm	48
5.3	MLME SAP interface	49
5.3.1	Resetting the MAC/MLME	50
5.3.1.1	MLME-RESET.request	50
5.3.1.2	MLME-RESET.confirm	50
5.3.2	Scanning for piconets	51
5.3.2.1	MLME-SCAN.request	53
5.3.2.2	MLME-SCAN.confirm	53
5.3.2.3	MLME-SCAN.indication	54
5.3.3	Starting a piconet	54
5.3.3.1	MLME-START.request	55
5.3.3.2	MLME-START.confirm	55
5.3.4	Stopping a piconet	55
5.3.4.1	MLME-STOP.request	56
5.3.4.2	MLME-STOP.confirm	56
5.3.5	Associating with a piconet	57
5.3.5.1	MLME-ASSOCIATE.request	58
5.3.5.2	MLME-ASSOCIATE.confirm	58
5.3.5.3	MLME-ASSOCIATE.indication	58
5.3.6	Disassociation from a piconet	58
5.3.6.1	MLME-DISASSOCIATE.request	59
5.3.6.2	MLME-DISASSOCIATE.confirm	59
5.3.6.3	MLME-DISASSOCIATE.indication	60
5.3.7	Security management	60
5.3.7.1	MLME-MEMBERSHIP-UPDATE.request	62
5.3.7.2	MLME-MEMBERSHIP-UPDATE.confirm	62
5.3.7.3	MLME-SECURITY-ERROR.indication	62
5.3.7.4	MLME-SECURITY-MESSAGE.request	62
5.3.7.5	MLME-SECURITY-MESSAGE.confirm	63
5.3.7.6	MLME-SECURITY-MESSAGE.indication	63
5.3.8	PNC handover	63
5.3.8.1	MLME-PNC-HANDOVER.indication	63
5.3.8.2	MLME-PNC-HANDOVER.response	64
5.3.8.3	MLME-NEW-PNC.indication	64
5.3.9	Requesting DEV information from the PNC	64
5.3.9.1	MLME-DEV-INFO.request	65
5.3.9.2	MLME-DEV-INFO.confirm	65
5.3.9.3	MLME-DEV-INFO.indication	65
5.3.10	Security information retrieval	65
5.3.10.1	MLME-SECURITY-INFO.request	65
5.3.10.2	MLME-SECURITY-INFO.confirm	66
5.3.10.3	MLME-SECURITY-INFO.indication	67
5.3.10.4	MLME-SECURITY-INFO.response	67
5.3.11	Application specific data management	67
5.3.11.1	MLME-APPLICATION-SPECIFIC.request	68
5.3.11.2	MLME-APPLICATION-SPECIFIC.confirm	69
5.3.11.3	MLME-APPLICATION-SPECIFIC.indication	69
5.3.12	Piconet services management	69
5.3.12.1	MLME-ANNOUNCE-SERVICE.request	70
5.3.12.2	MLME-ANNOUNCE-SERVICE.confirm	70
5.3.12.3	MLME-PICONET-SERVICES.request	71
5.3.12.4	MLME-PICONET-SERVICES.confirm	71

5.3.12.5	MLME-PICONET-SERVICES.indication	71
5.3.13	Stream management	71
5.3.13.1	MLME-CREATE-STREAM.request	73
5.3.13.2	MLME-CREATE-STREAM.confirm	74
5.3.13.3	MLME-CREATE-STREAM.indication	74
5.3.13.4	MLME-MODIFY-STREAM.request	74
5.3.13.5	MLME-MODIFY-STREAM.confirm	75
5.3.13.6	MLME-TERMINATE-STREAM.request	75
5.3.13.7	MLME-TERMINATE-STREAM.confirm	75
5.3.13.8	MLME-TERMINATE-STREAM.indication	75
5.3.14	Piconet parameter management	76
5.3.14.1	MLME-BSID-CHANGE.request	76
5.3.14.2	MLME-BSID-CHANGE.confirm	76
5.3.14.3	MLME-PICONET-PARM-CHANGE.indication	77
5.3.15	Power management	77
5.3.15.1	MLME-PS-SET-INFORMATION.request	79
5.3.15.2	MLME-PS-SET-INFORMATION.confirm	79
5.3.15.3	MLME-SPS-CONFIGURE.request	79
5.3.15.4	MLME-SPS-CONFIGURE.confirm	80
5.3.15.5	MLME-PM-MODE-CHANGE.request	80
5.3.15.6	MLME-PM-MODE-CHANGE.confirm	80
5.3.15.7	MLME-PM-MODE-CHANGE.indication	80
5.3.15.8	MLME-MONITOR-PM-MODE.request	81
5.3.15.9	MLME-MONITOR-PM-MODE.confirm	81
5.3.15.10	MLME-MONITOR-PM-MODE.indication	81
5.3.16	Multicast operations	82
5.3.16.1	MLME-MULTICAST-CONFIGURATION.request	83
5.3.16.2	MLME-MULTICAST-CONFIGURATION.confirm	83
5.3.16.3	MLME-MULTICAST-RX-SETUP.request	83
5.3.16.4	MLME-MULTICAST-RX-SETUP.confirm	84
5.3.17	Timing synchronization	84
5.3.17.1	MLME-BEACON-EVENT.request	84
5.3.17.2	MLME-BEACON-EVENT.confirm	84
5.3.17.3	MLME-BEACON-EVENT.indication	85
5.3.18	Transmit switched diversity (TSD)	85
5.3.18.1	MLME-TXDIV.request	85
5.3.18.2	MLME-TXDIV.confirm	86
5.4	MAC management	86
5.4.1	MAC PIB PNC group	86
5.4.2	MAC PIB characteristic group	87
5.5	MAC SAP	88
5.5.1	MAC-ASYNC-DATA.request	91
5.5.2	MAC-ASYNC-DATA.confirm	91
5.5.3	MAC-ASYNC-DATA.indication	91
5.5.4	MAC-ISOCH-DATA.request	92
5.5.5	MAC-ISOCH-DATA.confirm	92
5.5.6	MAC-ISOCH-DATA.indication	93
6.	MAC frame formats	94
6.1	Frame format conventions	94
6.2	General frame format	95
6.2.1	Frame Control field	96
6.2.1.1	Protocol Version field	96

6.2.1.2	Frame Type field.....	97
6.2.1.3	SEC field.....	97
6.2.1.4	ACK Policy field, Imp-ACK Request field, and Blk-ACK field	97
6.2.1.5	Retry field	97
6.2.1.6	More Data field.....	98
6.2.1.7	Imp-ACK Negative Acknowledgment (NAK) field.....	98
6.2.1.8	CTA Relinquish field.....	98
6.2.2	Piconet ID (PNID) field	99
6.2.3	SrcID and DestID fields	99
6.2.4	Fragmentation Control field	99
6.2.4.1	MSDU Number field	99
6.2.4.2	Fragment Number field.....	100
6.2.4.3	Last Fragment Number field.....	100
6.2.5	Stream Index field	100
6.2.6	MAC header validation	100
6.2.7	MAC Frame Body field	101
6.2.7.1	Frame Payload field.....	101
6.2.7.2	Secure session ID (SECID) field	101
6.2.7.3	Secure Frame Counter (SFC) field	101
6.2.7.4	Secure Payload field	101
6.2.7.5	Integrity Code field.....	101
6.2.7.6	Frame Check Sequence (FCS) field.....	101
6.2.8	SC and HSI aggregated frame format	102
6.2.8.1	Standard aggregation format.....	102
6.2.8.1.1	Non-secure standard aggregation format.....	102
6.2.8.1.2	Secure standard aggregation format	105
6.2.8.2	Low-latency aggregation formats	105
6.2.8.2.1	Non-secure low-latency aggregation format.....	105
6.2.8.2.2	Secure low-latency aggregation format	108
6.2.9	AV aggregated frame format	109
6.2.9.1	Extended MAC header format	109
6.2.9.1.1	Extended Control Header field	110
6.2.9.1.2	MAC Extension Header field	111
6.2.9.1.3	Security Header field	112
6.2.9.1.4	Video Header field.....	112
6.2.9.2	Subframe format	113
6.2.9.3	AV aggregated	115
6.2.9.4	Regular.....	115
6.2.9.5	Directional ACK	116
6.3	Format of individual frame types.....	116
6.3.1	Beacon frame	116
6.3.1.1	Non-secure Beacon frame.....	116
6.3.1.2	Secure Beacon frame	118
6.3.2	Acknowledgment frames	119
6.3.2.1	Imm-ACK frame.....	119
6.3.2.2	Delayed ACK (Dly-ACK) frame.....	120
6.3.3	Command frame	121
6.3.3.1	Non-secure Command frame	121
6.3.3.2	Secure Command frame.....	122
6.3.4	Data frame	123
6.3.4.1	Non-secure Data frame	123
6.3.4.2	Secure Data frame.....	123
6.3.5	Multi-protocol Data frame	124
6.3.5.1	Non-secure Multi-protocol Data frame.....	124

6.3.5.2	Secure Multi-protocol Data frame	125
6.3.6	Sync frame	125
6.4	Information elements (IEs)	126
6.4.1	CTA IE	128
6.4.2	BSID IE	129
6.4.3	Parent Piconet IE	129
6.4.4	DEV Association IE	129
6.4.5	PNC shutdown IE	130
6.4.6	Piconet Parameter Change IE	131
6.4.7	AS IE	132
6.4.8	Pending channel time map (PCTM) IE	132
6.4.9	PNC Handover IE	133
6.4.10	CTA Status IE	133
6.4.11	Capability IE	134
6.4.12	Transmit Power Parameters IE	140
6.4.13	PS Status IE	141
6.4.14	CWB IE	141
6.4.15	Overlapping PNID IE	142
6.4.16	Piconet Services IE	142
6.4.17	Vendor Defined IE	143
6.4.18	Group ID IE	143
6.4.19	Stream Renew IE	144
6.4.20	Next PNC IE	144
6.4.21	Piconet Channel Status IE	144
6.4.22	Synchronization IE	145
6.4.23	TSD IE	147
6.4.24	UEP Specific IE	148
6.4.25	IFS IE	148
6.4.26	CTA Relinquish Duration IE	149
6.4.27	Feedback IE	149
6.4.28	Mapping IE	151
6.4.29	BST Clustering IE	152
6.4.30	PET Clustering IE	152
6.4.31	Beam PET IE	153
6.4.32	HRS Beam PET IE	154
6.4.33	PET Amplitude IE	155
6.4.34	PET Phase IE	155
6.4.35	Sync Frame Frequency IE	156
6.4.36	Directional Peer IE	156
6.5	MAC commands	157
6.5.1	Association and disassociation commands	159
6.5.1.1	Association Request command	159
6.5.1.2	Association Response command	160
6.5.1.3	Disassociation Request command	161
6.5.2	Security commands	161
6.5.2.1	Request Key command	161
6.5.2.2	Request Key Response command	161
6.5.2.3	Distribute Key Request command	162
6.5.2.4	Distribute Key Response command	162
6.5.3	PNC handover commands	162
6.5.3.1	PNC Handover Request command	163
6.5.3.2	PNC Handover Response command	163
6.5.3.3	PNC Handover Information command	164
6.5.4	Information request commands	164

6.5.4.1	PNC Information Request command	164
6.5.4.2	PNC Information command	164
6.5.4.3	Security Information Request command	166
6.5.4.4	Security Information command	166
6.5.4.5	Probe Request command	167
6.5.4.6	Probe Response command	169
6.5.5	Information announcement commands	171
6.5.5.1	Piconet Services command	171
6.5.5.2	Announce command	171
6.5.5.3	Announce Response command	173
6.5.6	Channel time allocation request, modification, and termination commands	173
6.5.6.1	Channel Time Request command	173
6.5.6.2	Channel Time Response command	176
6.5.7	Channel status commands	177
6.5.7.1	Channel Status Request command	177
6.5.7.2	Channel status response	177
6.5.7.3	Remote Scan Request command	178
6.5.7.4	Remote Scan Response command	178
6.5.7.5	Transmit Power Change command	180
6.5.8	Power management commands	180
6.5.8.1	PS Set Information Request command	180
6.5.8.2	PS Set Information Response command	180
6.5.8.3	SPS Configuration Request command	181
6.5.8.4	SPS Configuration Response command	182
6.5.8.5	PM Mode Change command	183
6.5.8.6	PM Mode Change Response command	183
6.5.9	Special commands	184
6.5.9.1	Security Message command	184
6.5.9.2	Vendor Defined command	184
6.5.9.3	AS IE Request command	185
6.5.9.4	AS IE Response command	185
6.5.10	Multicast configuration commands	186
6.5.10.1	Multicast Configuration Request command	186
6.5.10.2	Multicast Configuration Response command	186
7.	MAC functional description	187
7.1	Introduction	187
7.2	Starting, maintaining, and stopping piconets	188
7.2.1	Scanning through channels	188
7.2.2	Starting a piconet	189
7.2.3	PNC handover	190
7.2.4	Preliminary handover	193
7.2.5	Next PNC	194
7.2.6	Dependent PNC handover	195
7.2.7	Child piconet	198
7.2.8	Neighbor piconet	200
7.2.9	Stopping piconet operations	202
7.2.9.1	Stopping an independent or parent piconet	203
7.2.9.2	Parent PNC stopping a dependent piconet	203
7.2.9.3	Dependent PNC termination of a dependent piconet	204
7.2.10	Non-PNC-capable DEVs	204
7.3	Association and disassociation with a piconet	204
7.3.1	Association	204

7.3.2	Piconet services	206
7.3.3	Broadcasting piconet information	208
7.3.4	Disassociation	209
7.4	Channel access	210
7.4.1	Interframe space (IFS)	211
7.4.2	Carrier sense multiple access with collision avoidance (CSMA/CA)	211
7.4.3	Channel time allocation period channel access	213
7.4.3.1	Channel time allocations (CTAs)	213
7.4.3.2	Channel time allocation (CTA) and channel time usage	215
7.4.3.3	Management CTAs	216
7.4.3.4	Slotted aloha access	216
7.4.3.5	Allocation of MCTAs	217
7.4.3.6	Guard time	217
7.4.3.7	Calculating channel time requests	219
7.4.3.8	Relinquishing CTA time to another DEV	220
7.5	Channel time management	222
7.5.1	Isochronous stream management	222
7.5.1.1	Isochronous stream creation	223
7.5.1.2	Isochronous stream modification	226
7.5.1.3	Isochronous stream termination	229
7.5.2	Asynchronous channel time reservation and termination	231
7.5.2.1	Asynchronous channel time reservation	231
7.5.2.2	Asynchronous channel time termination	233
7.5.3	Multicast group configuration	234
7.6	Synchronization	235
7.6.1	Time accuracy	236
7.6.2	Beacon generation	236
7.6.3	Beacon reception	237
7.6.4	Beacon information announcement	237
7.6.5	Superframe support for directional PHYs	238
7.6.5.1	Quasi-omni beacon	239
7.6.5.2	Directional CAP	240
7.6.5.3	Directional association	241
7.6.5.4	DEV quasi-omni transmit direction training and tracking	242
7.7	Fragmentation and defragmentation	243
7.8	Aggregation	244
7.8.1	Standard aggregation	244
7.8.2	Low-latency aggregation	245
7.9	Acknowledgment and retransmission	246
7.9.1	No acknowledgment (no-ACK)	246
7.9.2	Immediate acknowledgment (Imm-ACK)	246
7.9.3	Delayed acknowledgment (Dly-ACK)	247
7.9.4	Implied acknowledgment (Imp-ACK)	248
7.9.5	Block acknowledgment (Blk-ACK)	250
7.9.5.1	Blk-ACK for standard aggregation	250
7.9.5.2	Blk-ACK for low-latency aggregation	251
7.9.6	Retransmissions	252
7.9.7	Duplicate detection	252
7.10	Peer discovery	252
7.10.1	PNC information request	252
7.10.2	Probe request and response	253
7.10.3	Announce	254
7.10.4	Channel status request	254
7.10.5	Remote scan	254

7.10.6	PNC channel scanning	255
7.10.7	Channel probing	255
7.11	Changing piconet parameters.....	256
7.11.1	Moving beacon	256
7.11.2	Changing superframe duration	256
7.11.3	Setting the PNID or BSID	257
7.11.4	Maintaining synchronization in dependent piconets	258
7.12	Interference mitigation.....	258
7.12.1	Dynamic channel selection	259
7.12.2	Transmit power control	260
7.12.2.1	Maximum transmitter power for the CAP, beacon, and directed MCTAs..	260
7.12.2.2	Adjustable transmitter power in a CTA.....	261
7.13	Multi-rate support	261
7.14	Power management.....	262
7.14.1	Piconet synchronized power save (PSPS) mode	263
7.14.2	Device synchronized power save (DSPS) mode	264
7.14.2.1	Creation, use, and management of DSPS sets	264
7.14.2.2	Changing DSPS mode and operation.....	265
7.14.2.3	CTA timing in DSPS mode	266
7.14.3	Asynchronous power save (APS) mode	268
7.14.4	MSCs for power save modes	269
7.15	AS IE operation	272
7.16	MAC sublayer parameters	275
7.17	Unequal error protection (UEP).....	278
7.18	Sync frame transmission and virtually dependent piconet	278
8.	Security	280
8.1	Security mechanisms	280
8.1.1	Security membership and key establishment	280
8.1.2	Key transport	280
8.1.3	Data encryption	280
8.1.4	Data integrity	280
8.1.5	Beacon integrity protection	280
8.1.6	Command integrity protection	281
8.1.7	Freshness protection	281
8.2	Security modes.....	281
8.2.1	Security mode 0	281
8.2.2	Security mode 1	281
8.3	Security support	281
8.3.1	PNC handover	281
8.3.2	Changes in the piconet group data key	282
8.3.3	Joining a secure piconet	282
8.3.4	Membership update	282
8.3.5	Secure frame generation	283
8.3.6	Updating CurrentTimeToken	284
8.3.7	Secure frame reception	284
8.3.8	Selecting the SECID for a new key	285
8.3.9	Key selection	285
8.4	Protocol details	289
8.4.1	Security information request and distribution	289
8.4.2	Key distribution protocol	291
8.4.3	Key request protocol	291

9.	Security specifications	292
9.1	Modes for security	292
9.2	Symmetric cryptography building blocks	292
9.2.1	Notational conventions	292
9.2.2	CCM combined encryption and data authentication	292
9.2.3	CCM parameters	292
9.2.4	Nonce value	292
9.2.5	AES encryption	293
9.3	Symmetric cryptography implementation	293
9.3.1	Symmetric cryptography data formats	293
9.3.2	Symmetric cryptographic operations	293
9.4	CCM mode.....	295
9.4.1	Inputs	295
9.4.2	Data authentication	296
9.4.3	Encryption	298
9.4.4	Output	298
9.4.5	Decryption	299
9.4.6	Restrictions	299
9.4.7	List of symbols	299
10.	PHY specification for the 2.4 GHz band	301
10.1	Overview of the 2.4 GHz PHY	301
10.2	General requirements.....	302
10.2.1	Operating frequency range	302
10.2.2	Radio frequency (RF) power measurements	302
10.2.3	Channel assignments	302
10.2.4	Scanning channels	302
10.2.5	Unwanted emissions	303
10.2.6	Operating temperature range	303
10.2.7	PHY layer timing	303
10.2.7.1	Interframe space.....	303
10.2.7.2	Receive-to-transmit turnaround time	303
10.2.7.3	Transmit-to-receive turnaround time	304
10.2.7.4	Time between successive transmissions	304
10.2.7.5	Channel switch time.....	304
10.2.8	Data size restrictions	304
10.2.8.1	Maximum frame length	304
10.2.8.2	Maximum transfer unit size	304
10.2.8.3	Minimum fragment size.....	304
10.2.9	Header check sequence	304
10.2.10	Channel access methods	306
10.3	Modulation and coding	306
10.3.1	Base data rate	307
10.3.2	Signal constellations	307
10.3.3	DQPSK modulation	308
10.3.4	QPSK and 16/32/64-QAM with trellis coding	309
10.4	PHY frame format	316
10.4.1	Frame format	316
10.4.2	PHY preamble	317
10.4.3	Header modulation	319
10.4.4	Scrambling	319
10.4.5	PHY header	321

10.4.6	Stuff bits	322
10.4.7	Tail symbols	322
10.5	Transmitter specifications	325
10.5.1	Error vector magnitude definition	325
10.5.2	EVM calculated values	326
10.5.3	Transmit power spectral density (PSD) mask	326
10.5.4	Transmit center frequency tolerance	326
10.5.5	Symbol rate	326
10.5.6	Clock synchronization	327
10.5.7	Transmit power-on and power-down ramp	327
10.5.8	RF carrier suppression	327
10.5.9	Transmit power	327
10.6	Receiver specifications	328
10.6.1	Error rate criterion	328
10.6.2	Receiver sensitivity	328
10.6.3	Receiver maximum input level	329
10.6.4	Receiver jamming resistance	329
10.6.5	Receiver CCA performance	330
10.6.6	Receiver RSSI	330
10.6.7	Link quality indication	330
10.7	PHY management	330
11.	PHY specification for millimeter wave	333
11.1	General requirements	333
11.1.1	Regulatory information	333
11.1.2	RF power measurements	334
11.1.3	Unwanted emissions	334
11.1.4	Operating temperature range	334
11.1.5	RF channelization	334
11.1.6	Transmit PSD mask	334
11.1.7	Error vector magnitude calculation	334
11.1.7.1	SC PHY	334
11.1.7.2	AV and HSI PHYs	335
11.1.8	Common PHY management for mmWave PHY modes	336
11.1.8.1	Supported MCSs	336
11.1.8.2	Preferred fragment size	336
11.1.8.3	Receive Status field	337
11.1.9	Requirements for mmWave PNCs	338
11.1.10	CP operation	338
11.1.11	mmWave PHY mode usage in CTA	339
11.1.12	Common mode signaling (CMS)	339
11.1.12.1	Forward error correction for CMS	340
11.1.12.2	Code spreading for CMS	340
11.1.12.3	Scrambling for CMS	340
11.1.12.4	PHY preamble for CMS	341
11.1.12.5	Frame header for CMS	341
11.1.12.6	PHY header for CMS	342
11.1.12.7	PHY Payload field for CMS	343
11.1.12.8	Receiver clear channel assessment performance for CMS	343
11.1.13	mmWave PHY PIB	343
11.2	Single Carrier Mode of mmWave PHY	344
11.2.1	PHY operating specifications of SC PHY	345
11.2.1.1	Channelization	345

11.2.1.2	Scanning channels.....	345
11.2.2	Modulation, forward error correction, and spreading	345
11.2.2.1	MCS-dependent parameters.....	345
11.2.2.2	Header rate-dependent parameters.....	347
11.2.2.3	Timing-related parameters	348
11.2.2.4	Frame-related parameters	348
11.2.2.5	Modulation.....	349
11.2.2.5.1	p/2 BPSK	349
11.2.2.5.2	p/2 QPSK	349
11.2.2.5.3	p/2 8-PSK.....	350
11.2.2.5.4	p/2 16-QAM.....	351
11.2.2.6	FEC	351
11.2.2.6.1	Reed-Solomon block codes in GF(28).....	351
11.2.2.6.2	Irregular LDPC codes	352
11.2.2.6.3	Rate 14/15 LDPC code	353
11.2.2.7	Stuff bits.....	353
11.2.2.8	Code spreading	356
11.2.2.8.1	Golay sequences	356
11.2.2.8.2	PRBS generation with LFSR	356
11.2.2.9	Unequal error protection.....	357
11.2.2.10	Scrambling.....	358
11.2.3	SC PHY frame format	359
11.2.3.1	PHY preamble.....	360
11.2.3.1.1	Sync field	360
11.2.3.1.2	SFD field.....	360
11.2.3.1.3	Channel estimation sequence (CES).....	360
11.2.3.2	Frame header.....	360
11.2.3.2.1	SC PHY header	362
11.2.3.2.2	Base header HCS	363
11.2.3.2.3	Base header FEC.....	363
11.2.3.2.4	MAC subheader HCS	363
11.2.3.2.5	MAC subheader FEC.....	364
11.2.3.3	SC PHY Payload field	364
11.2.3.3.1	SC PHY Payload scrambling.....	364
11.2.3.3.2	Modulation.....	364
11.2.3.3.3	FEC	364
11.2.3.3.4	Code spreading	364
11.2.3.4	Pilot word and PCES	365
11.2.3.4.1	Subblocks and pilot word	365
11.2.3.4.2	Pilot channel estimation sequence (PCES).....	365
11.2.4	Transmitter specifications	366
11.2.4.1	Error vector magnitude	366
11.2.4.2	Transmit center frequency tolerance.....	366
11.2.4.3	Symbol rate.....	366
11.2.4.4	Transmit power-on and power-down ramp	366
11.2.5	Receiver specifications	366
11.2.5.1	Error rate criterion	366
11.2.5.2	Receiver sensitivity.....	367
11.2.5.3	Receiver maximum input level.....	367
11.2.5.4	Receiver clear channel assessment performance	367
11.2.6	PHY layer timing	368
11.2.6.1	Interframe space.....	368
11.2.6.2	Receive-to-transmit turnaround time	368
11.2.6.3	Transmit-to-receive turnaround-time.....	368

11.2.6.4	Time between successive transmissions	368
11.2.6.5	Channel switch.....	369
11.2.7	PHY management for SC PHY	369
11.2.7.1	Maximum frame size	369
11.2.7.2	Maximum transfer unit size	369
11.2.7.3	Minimum fragment size.....	369
11.2.8	Optional OOK/DAMI modes	369
11.2.8.1	OOK.....	369
11.2.8.2	DAMI.....	370
11.2.8.3	FEC	370
11.2.8.4	OOK/DAMI spreading	370
11.3	High Speed Interface mode of mmWave PHY	370
11.3.1	General operating specifications	370
11.3.1.1	Operating frequency bands	370
11.3.2	HSI PHY modulation, forward error correction, and spreading	370
11.3.2.1	MCS-dependent parameters.....	370
11.3.2.2	HSI PHY timing-related parameters.....	372
11.3.2.3	HSI PHY frame-related parameters	373
11.3.2.4	HSI PHY FEC.....	373
11.3.2.4.1	LDPC block code.....	374
11.3.2.4.2	EEP data multiplexer	374
11.3.2.4.3	UEP data multiplexer.....	374
11.3.2.4.4	Bit interleaver	375
11.3.2.5	Stuff bits.....	376
11.3.2.6	Constellation mapping	376
11.3.2.7	HSI spreader	378
11.3.2.7.1	Spreader for spreading factor of 1	379
11.3.2.7.2	Spreader for spreading factor of 48	379
11.3.2.8	Tone interleaver	379
11.3.2.9	HSI PHY OFDM modulator	380
11.3.2.9.1	Pilot subcarriers	381
11.3.2.9.2	Guard subcarriers.....	382
11.3.2.10	PCES insertion.....	382
11.3.2.11	HSI PHY scrambling	382
11.3.3	HSI PHY frame format	383
11.3.3.1	PHY preamble.....	383
11.3.3.2	Frame header.....	384
11.3.3.3	HSI PHY header	386
11.3.3.4	Header check sequences	387
11.3.3.4.1	Main Header HCS.....	387
11.3.3.4.2	MAC Subheader HCS.....	387
11.3.3.5	PHY Payload field	388
11.3.4	Transmitter specifications	388
11.3.4.1	EVM requirement	388
11.3.4.2	Chip rate and clock alignment	389
11.3.5	Receiver specifications	389
11.3.5.1	Receiver sensitivity.....	389
11.3.5.2	Receiver CCA performance.....	389
11.3.5.3	Receiver maximum input level.....	389
11.3.5.4	PHY layer timing	389
11.3.5.5	Interframe spacing	389
11.3.5.6	Receive-to-transmit turnaround time	390
11.3.5.7	Transmit-to-receive turnaround time	390
11.3.5.8	Time between successive transmissions	390

11.3.5.9	Channel switch time.....	390
11.3.6	HSI PHY management	390
11.3.6.1	PHY supported data rate encoding	390
11.3.6.2	HSI PHY fragment size encoding.....	390
11.3.6.3	Maximum frame length	391
11.3.6.4	Maximum transfer unit size	391
11.3.6.5	Minimum fragment size.....	391
11.4	Audio/Visual mode of mmWave PHY	391
11.4.1	General requirements	392
11.4.1.1	AV PHY channelization	392
11.4.1.2	PHY layer timing.....	393
11.4.1.2.1	Interframe space.....	393
11.4.1.2.2	Receive-to-transmit turnaround time.....	394
11.4.1.2.3	Transmit-to-receive turnaround time.....	394
11.4.1.2.4	Time between successive transmissions	394
11.4.1.2.5	Channel switch time.....	394
11.4.1.2.6	CCA detect time.....	394
11.4.1.3	Data size restrictions	394
11.4.1.3.1	Maximum frame length	394
11.4.1.3.2	Maximum transfer unit size	395
11.4.1.3.3	Minimum fragment size.....	395
11.4.1.4	Header check sequence.....	395
11.4.2	AV PHY modulation and forward error correction	395
11.4.2.1	AV PHY base rate.....	396
11.4.2.2	Repetition coding and spatial diversity.....	397
11.4.2.3	Stuff bits.....	397
11.4.2.4	HRP splitter and scrambler	398
11.4.2.5	LRP scrambler	398
11.4.2.6	HRP outer code	399
11.4.2.7	HRP outer interleaver	399
11.4.2.8	Convolutional encoder	400
11.4.2.9	Puncturing.....	400
11.4.2.10	HRP data multiplexer and bit interleaver	400
11.4.2.10.1	EEP data multiplexer	401
11.4.2.10.2	UEP coding data multiplexer	402
11.4.2.10.3	UEP mapping data multiplexer	404
11.4.2.10.4	HRP header data multiplexer	405
11.4.2.11	Bit reversal tone interleaver	406
11.4.2.12	Signal constellations	406
11.4.2.13	AV PHY non-data subcarriers	407
11.4.2.14	AV PHY OFDM modulation	408
11.4.3	AV PHY frame formats	409
11.4.3.1	HRP preamble.....	410
11.4.3.2	HRP header	411
11.4.3.3	LRP preamble sequences	411
11.4.3.4	Long omni LRP preamble.....	412
11.4.3.5	Short omni LRP preamble	413
11.4.3.6	Omni LRP header	414
11.4.3.7	Directional LRP preamble	414
11.4.3.8	Directional LRP header and payload	415
11.4.4	AV PHY transmitter requirements	416
11.4.4.1	TX mask.....	416
11.4.4.2	EVM requirement	417
11.4.4.3	Symbol timing.....	417

11.4.4.4	TX frequency accuracy	418
11.4.4.5	TX power ramp on and off	418
11.4.5	AV PHY Receiver characteristics	418
11.4.5.1	Error rate criterion	418
11.4.5.2	Sensitivity	418
11.4.5.3	Maximum input level.....	418
11.4.6	Preambles and training symbols	418
12.	Beam forming	423
12.1	Introduction.....	423
12.2	Beam forming terminology.....	423
12.2.1	Quasi-omni patterns	424
12.2.2	Sectors	424
12.2.3	Beams	425
12.2.4	Clusters	426
12.3	Beam forming codebooks	427
12.3.1	Beam forming codebooks	428
12.4	Beam forming reference model	429
12.5	Beam forming protocol	431
12.5.1	Two-level training mechanism	431
12.5.1.1	Sector-level training.....	431
12.5.1.1.1	AAS sector-level training	431
12.5.1.1.2	SAS sector-level training	434
12.5.1.1.3	Sector-level training failure remedy	437
12.5.1.2	Beam-level training.....	437
12.5.1.2.1	AAS beam-level training	437
12.5.1.2.2	SAS beam-level training.....	440
12.5.2	Beam tracking	443
12.6	On-demand beam forming	445
12.7	Proactive beam forming	445
12.8	TSD.....	445
Annex A	(informative) Bibliography	447
Annex B	(normative) Frame convergence sublayer	448
B.1	Generic convergence sublayer	448
B.2	EPD FCSL PDU classification	449
B.3	EPD FCSL	449
B.3.1	EPD FCSL QoS support	450
B.3.2	Data entity inter-relationships.....	450
B.4	EPD FCSL SAP	451
B.4.1	MA-UNITDATA.request	452
B.4.2	MA-UNITDATA.indication	452
B.4.3	MA-UNITDATA-STATUS.indication.....	453
B.5	Stream SAP	454
B.5.1	Stream creation, modification, and deletion	454
B.5.1.1	STREAM_INITIATE.request.....	456
B.5.1.2	STREAM_INITIATE.confirm.....	456
B.5.1.3	STREAM_INITIATE.indication	456
B.5.1.4	STREAM_MODIFY.request	457
B.5.1.5	STREAM_MODIFY.confirm	457
B.5.1.6	STREAM_END.request.....	457

B.5.1.7	STREAM_END.confirm.....	458
B.5.1.8	STREAM_END.indication.....	458
B.5.2	Stream data interface.....	458
B.5.2.1	STREAM_DATA.request.....	459
B.5.2.2	STREAM_DATA.confirm.....	460
B.5.2.3	STREAM_DATA.indication.....	460
Annex C (informative)	Security considerations.....	461
C.1	Background assumptions.....	461
C.1.1	Physical assumptions.....	461
C.1.2	Network assumptions.....	461
C.1.3	Attack model assumptions.....	462
C.1.4	Security key lifecycle issues.....	462
C.1.4.1	Key lifecycle.....	462
C.1.4.2	Membership lifecycle.....	462
C.1.4.3	Group membership change rekey.....	462
C.2	Claimed security services.....	462
C.2.1	Beacon protection protocol.....	462
C.2.2	Distribute key protocol.....	463
C.2.3	Key request protocol.....	463
C.2.4	Data protection protocol.....	464
C.3	Properties of the IEEE 802.15.3 security suite.....	464
C.3.1	Key usage.....	464
C.3.2	Replay prevention.....	464
Annex D (informative)	Coexistence, interoperability, and interference.....	466
D.1	Interoperability.....	466
D.1.1	Interoperability with IEEE 802.11 DSSS and IEEE 802.11b.....	466
D.1.2	IEEE 802.11 FHSS and IEEE 802.15.1.....	467
D.2	Coexistence.....	467
D.2.1	Coexistence with IEEE Std 802.11b.....	467
D.2.1.1	Passive scanning.....	468
D.2.1.2	Dynamic channel selection.....	468
D.2.1.3	The ability to request channel quality information.....	468
D.2.1.4	Link quality and RSSI.....	468
D.2.1.5	Channel plan that minimizes channel overlap.....	468
D.2.1.6	Lower transmit power.....	469
D.2.1.7	Transmit power control.....	469
D.2.1.8	Neighbor piconet capability.....	469
D.2.2	Coexistence with IEEE 802.15.1 and IEEE 802.11 FHSS.....	470
D.2.2.1	PHY collaborative coexistence enhancements.....	470
D.2.2.2	MAC coexistence via collaboration.....	470
D.2.2.3	Other techniques.....	471
D.3	Coexistence performance.....	471
D.3.1	Allowed operation.....	471
D.3.2	Assumptions for coexistence calculations.....	471
D.3.3	Performance impact on IEEE 802.15.3 piconets.....	473
D.3.3.1	IEEE 802.11b overlapping with IEEE 802.15.3.....	473
D.3.3.2	IEEE 802.15.1 and IEEE 802.11 FHSS overlapping with IEEE 802.15.3.....	476
D.4	Notes on the calculations.....	477

Annex E (normative) Protocol implementation conformance statement (PICS) proforma.....	478
E.1 Introduction.....	478
E.1.1 Scope.....	478
E.1.2 Purpose.....	478
E.2 Abbreviations and special symbols.....	478
E.3 Instructions for completing the PICS proforma.....	479
E.4 Identification of the implementation.....	479
E.5 Identification of the protocol	480
E.6 Global statement of conformance	481
E.7 PICS proforma—IEEE Std 802.15.3-2016.....	481
E.7.1 Major roles for IEEE 802.15.3 DEVs.....	481
E.7.2 PHY functions.....	482
E.7.3 Major capabilities for the MAC sublayer	483
E.7.3.1 MAC frames	483
E.7.3.2 MAC sublayer functions	486
E.7.4 Security support	490
Annex F (informative) Implementation considerations.....	491
F.1 Channel time requests.....	491
F.1.1 Types of CTAs.....	491
F.1.2 Interpretation of channel time requests.....	492
F.1.3 Determining CTA Rate Factor from stream requirements	493
F.1.3.1 Example 1.....	494
F.1.3.2 Example 2.....	495
F.1.4 PNC interpretation of CTA rate factor	495
F.1.5 Creating channel time requests from MLME requests	496
F.1.6 Interpreting channel time requests.....	498
F.2 Sample frames.....	500
F.3 Use of multiple mmWave PHYs in a single piconet	502
Annex G (normative) Optional OOK/DAMI modes	504
G.1 Introduction.....	504
G.2 Child piconet operation.....	504
G.3 DAMI.....	504
G.4 PHY preamble.....	506
G.5 PHY frame format	507
G.6 Interframe space.....	507
G.7 Eye opening for OOK	508
G.8 EVM for DAMI	508

IEEE Standard for High Data Rate Wireless Multi-Media Networks

IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

1. Overview

1.1 Scope

This standard defines PHY and MAC specifications for high data rate wireless connectivity (typically over 200 Mbps) with fixed, portable, and moving devices. Data rates are high enough to satisfy a set of consumer multimedia industry needs, as well as to support emerging wireless switched point-to-point and high rate close proximity point-to-point applications.

1.2 Purpose

The purpose of this standard is to provide for low complexity, low cost, low power consumption, and high data rate wireless connectivity among devices that support a variety of applications such as a set of consumer multimedia industry needs, wireless switched point-to-point applications in data centers, wireless backhaul/fronthaul intra-device communications, and a wide variety of additional use cases such as rapid large multimedia data downloads and file exchanges between two devices in close proximity, including between mobile devices and stationary devices (kiosks, ticket gates, etc.), and/or wireless data storage devices.

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used; therefore, each referenced document is cited in the text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

ANSI X3.66-1979: Advanced data communication control procedures (ADCCP).¹

IEEE Std 802[®]-2014, IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture.^{2, 3}

ISO/IEC 646:1991, Information Technology—ISO 7-bit coded character set for information interchange.⁴

NIST FIPS Pub 197: Advanced Encryption Standard (AES), Federal Information Processing Standards Publication 197, US Department of Commerce/N.I.S.T., November 26, 2001.⁵

¹ ANSI publications are available from the American National Standards Institute (<http://www.ansi.org>).

² IEEE publications are available from the Institute of Electrical and Electronics Engineers (<http://standards.ieee.org>).

³ The IEEE standards referred to in Clause 2 are trademarks belonging to the Institute of Electrical and Electronics Engineers, Inc.

⁴ ISO/IEC publications are available from the International Organization for Standardization (<http://www.iso.ch/>) and the International Electrotechnical Commission (<http://www.iec.ch/>). ISO/IEC publications are also available in the United States from the American National Standards Institute (<http://www.ansi.org>).

⁵ NIST FIPS publications are available from the National Institute for Standards and Technology (<http://www.nist.gov>).