



INTERNATIONAL STANDARD ISO/IEC 23007-1:2010/Amd.1:2012 TECHNICAL CORRIGENDUM 1

Published 2012-09-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Rich media user interfaces — Part 1: Widgets

AMENDMENT 1: Widget extensions

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Interfaces d'utilisateur au support riche —

Partie 1: Widgets

AMENDEMENT 1: Extensions de widget

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 23007-1:2010/Amd.1:2012 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

In 6.1, replace the following paragraph:

A widget manager can then request the migration of a widget from the target widget manager using the `getWidget` message. This message instructs the target widget manager to trigger the migration of the widget whose code is provided. The target widget manager then sends a `startWidget` message to the widget manager originating this message. The following error codes are defined:

with:

A widget manager can then request the migration of a widget from the target widget manager using the `getWidget` message. This message instructs the target widget manager to trigger the migration of the widget whose code is provided. The target widget manager then receives the equivalent of a `startWidget` message as a response to the `getWidget` message. The following error codes are defined:

At the end of 6.1, replace in the pseudo-code the definition of the `getWidget` message:

```
<mw:messageIn name="getWidget">
  <mw:input name="widgetCode" scriptParamType="number"/>
  <mw:output name="errorCode" scriptParamType="number"/>
</mw:messageIn>
```

with:

```
<mw:messageIn name="getWidget">
  <mw:input name="widgetCode" scriptParamType="number"/>
  <mw:output name="errorCode" scriptParamType="number"/>
  <mw:output name="widgetUrl" scriptParamType="string"/>
  <mw:output name="widgetUUID" scriptParamType="string"/>
  <mw:output name="widgetContext" scriptParamType="string"/>
</mw:messageIn>
```